

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 23 N., R. 63 E.

CHAINS	<p style="text-align: center;">T23N R63E R64E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1964</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy and gravelly alkaline clay loam. Timber, none; undergrowth, sparse rabbit brush and sagebrush.</p>
	<p>N. 0° 31' E., bet. secs. 1 and 6.</p> <p>Over nearly level meadow land.</p>
31.10	<p>Road, improved, oil surfaced, bears N. 82° W., to Cherry Creek, and S. 82° E., to junction of U. S. Highway 93 and Alternate 50.</p>
41.13	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
82.26	<p style="text-align: center;">T23N R63E R64E ½ S 1 S 6</p> <p style="text-align: center;">1964</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Leave meadow land, enter medium heavy undergrowth; edge bears E. and W.</p> <p>The cor. of Tps. 23 and 24 N., Rs. 63 and 64 E., monumented with the remains of a squared wooden post, 4 ins. diam., badly decayed, loosely set in the ground, with scribe marks dimly visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R63E R64E S 36 S 31 S 1 S 6 T23N</p> <p style="text-align: center;">1964</p>