

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 24 N., R. 63 E.

CHAINS

T24N			
R63E		R64E	
S	1	S	6
S	12	S	7
1964			

raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly alkaline clay loam.

Timber, none; undergrowth, sagebrush and rabbit brush.

N. 0° 10' E., bet. secs. 1 and 6.

Over nearly level land, through scattering undergrowth.

8.50 Leave pastureland, enter heavy undergrowth, edge bears NE. and SW.

40.20 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T24N			
R63E		R64E	
S	1	S	6
	¼		
1964			

raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

40.40 Fence, bears E. and W.

47.70 Road, unimproved, bears NE. and SW.

54.30 Telephone pole line, old, abandoned bears NE. and SW.

71.70 Road, semi-improved, bears NE. and SW.

77.40 Road, unimproved, bears E. and W.

80.40 The cor. of Tps. 24 and 25 N., Rs. 63 and 64 E., monumented with a limestone, 16x14x4 ins., firmly set in a mound of stone, and plainly mkd. with 6 notches on the N., E., S., and W. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.