

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 25 N., R. 63 E.

CHAINS

Reestablishment of the Survey Executed by Winfred
A. Pray, Deputy Surveyor, in 1909

Beginning at the cor. of Tps. 24 and 25 N., Rs. 63 and 64 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of the East bdy., T. 24 N., R. 63 E.

NORTH, bet. secs. 31 and 36.

Over nearly level land, through scattering undergrowth.

30.70 Road, unimproved, bears E. and W.

39.96 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a limestone, 16x8x4 ins., firmly set in the ground, and in a collar of stone, plainly mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T25N
R63E R64E
 $\frac{1}{4}$
S 36 | S 31
1964

bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

NORTH, beginning new measurement.

Continue over nearly level land through scattering undergrowth.

37.70 Wash, 10 lks. wide, 3 ft. deep, drains E.

39.94 The cor. of secs. 25, 30, 31 and 36, monumented with a limestone, 14x8x4 ins., firmly set in the ground and in a collar of stone, plainly marked with 1 notch on S. face, and 5 notches on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T25N
R63E R64E
S 25 | S 30
S 36 | S 31
1964

bury the cornerstone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.