

DEPENDENT RESURVEY OF THE EAST BOUNDARY  
T. 25 N., R. 63 E.

CHAINS  
26.70

Road; unimproved, bears WSW. and ENE.

28.60

Fence, bears WNW. and ESE.

39.97

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, monumented with a limestone, 14x8x6 ins., firmly set in the ground, and in a mound of stone, plainly mkd.  $\frac{1}{4}$  on W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground with brass cap mkd.

T25N  
R63E R64E  
 $\frac{1}{4}$   
S 12 | S 7  
1964

bury the cornerstone alongside the iron post, and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

N.  $0^{\circ} 02' W.$ , beginning new measurement.

Continue over slightly rolling land; asc, 60 ft, over SE. slope.

39.90

The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 14x8x8 ins., firmly set in the ground and in a mound of stone, plainly mkd. with 5 notches on S. face, and 1 notch on N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T25N  
R63E R64E  
S 1 | S 6  
S 12 | S 7  
1964

bury the cornerstone alongside the iron post.

Land, slightly rolling.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, sagebrush and rabbit brush.

N.  $0^{\circ} 01' W.$ , bet. secs. 1 and 6.

Over rolling land, through medium heavy undergrowth; asc. 60 ft. over ESE. slope.

19.50

Wash, 30 lks. wide, 6 ft. deep, drains E.

21.10

Road, unimproved, bears E. and W.

22.20

Top of ascent, slopes E., begin descent; desc. 10 ft. over N. slope.