		DEPENDENT RESURVEY OF THE E. BDY., T. 19 N., R. 43 E.
	chains 14.40	Small spur, slopes W.
	15.00	Track road, bears E. and W.
ļ	18.40	Track road, bears E. and WNW.; desc. 40 ft. over N. slope.
	24.30	Wash, 20 lks. wide, 3 ft. deep, drains W.; asc. 10 ft. over steep S. slope.
	26.36	The cor. of secs. 6 and 7, monumented with a granite stone, 14x12x8 ins., firmly set and plainly mkd. as described in the official records.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to cap, with brass cap mkd.
		T19N R43E R44E S 12 S 6 S 7
		1964
		bury original corner stone alongside the iron post.
		N. 0° 51' E., bet. secs. 6 and 12, beginning new measurement.
		Asc. 40 ft. over S. slope, then over gently rolling terrain.
	13.38	The original cor. of secs. 1 and 12, monumented with the remains of a wooden post, bearing dim scribe mks. and a granite stone, 12x10x9 ins., firmly set and unmarked. This corner now becomes an angle point on the east bdy. of sec. 12.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.
		T19N R43E R44E AP S 12 S 6
		1964
		reset the remains of wooden post and granite stone along- side the iron post.
		Land, rolling W. slope. Soil, sandy loam and rocky. Vegetation, sagebrush and sparse native grasses. Timber, scattered pinon pine and juniper.
		N. 0° 29' E., bet. secs. 6 and 12.
:		Over gently rolling terrain, draining W., through dense low brush.
	1.40	The closing sec. cor. of secs. 1 and 12, hereinafter described.
		Thence bet. secs. 1 and 6.
	4.00	Small wash, drains W.; asc. 40 ft. over S. slope.