

SURVEY OF A PORTION OF SUBDIVISIONAL LINES COMPLETING THE
SUBDIVISION OF T. 19 N., R. 43 E.

CHAINS

79.50

Intersect the N. bdy. of the Tp.
Point for the closing cor. of secs. 1 and 2.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T20N R43E
S 35
S 2 | S 1
CC
T19N R43E

1964

From this corner, the cor. of secs. 35 and 36, T. 20 N., R. 43 E., bears S. 89° 24' E., 3.69 chs. dist.
Land, gently rolling.
Soil, sandy loam.
Vegetation, sagebrush.

Point for the N. ¼ sec. cor. of sec. 1, on the N. bdy. of the Tp. and at 40.00 chs. departure from the closing corner of secs. 1 and 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T20N R43E
¼ S 1
T19N R43E

1964

From this corner, the ¼ sec. cor. of sec. 36, bears S. 89° 24' E., 3.73 chs. dist.

From the cor. of secs. 25, 26, 35 and 36.
WEST, bet. secs. 26 and 35.
Over gently rolling land, draining W.
Desc. 130 ft. over rolling W. slope to ¼ sec. cor.

20.10

Fence, bears N. and S.

40.00

Point for the ¼ sec. cor. of secs. 26 and 35.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T19N R43E
S 26
¼ S 35

1964

deposit broken glass at base of iron post.
Desc. 100 ft. over rolling W. slope to closing cor.