

SURVEY OF A PORTION OF SUBDIVISIONAL LINES COMPLETING THE
SUBDIVISION OF T. 19 N., R. 43 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T19N R43E

S 3 $\frac{1}{2}$ | S 2

1964

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

43.40 Telephone line, parallels Nevada State Highway No. 8A.

80.42 Intersect the N. bdy. of the Tp.

Point for the closing corner of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N R43E

S 34
S 3 | S 2

CC

T19N R43E

1964

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

From the corner, the cor. of secs. 34 and 35, T. 20 N., R. 43 E., bears S. $89^{\circ} 24'$ E., 3.75 chs. dist.

Land, gently rolling.

Soil, sandy clay.

Vegetation, crested wheat grass, reseeded.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 2, on the N. bdy. of the Tp. and at midpoint on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T20N R43E

$\frac{1}{4}$ S 2

T19N R43E

1964

deposit broken glass at base of iron post.

From this corner, the $\frac{1}{4}$ sec. cor. of sec. 35, T. 20 N., R. 43 E., bears S. $89^{\circ} 24'$ E., 3.72 chs. dist.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, on the N. bdy. of the Tp. and at 40.00 chs. departure from the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.