

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH RANGE 38 EAST, MDM., NEVADA

CHAINS	
	bury the remains of the mkd. pinon tree alongside the iron post.
	Land, mountainous. Soil, rocky and sandy loam. Timber, juniper and pinon trees.
	S. 89° 54' W., along the S. bdy. of sec. 32.
	Over rolling mountainous land, draining S.; desc. 50 ft. through pinon pine and junipers.
4.45	The standard cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Thence along the S. bdy. of sec. 31, continuing measurement.
18.50	Head of ravine, course S.; asc. 70 ft. over an E. slope.
23.50	Top of Desatoya Mountains, bears NE. and SW.; desc. 150 ft. over a broken NW. slope.
28.50	Ravine, course NW.; desc. 230 ft. over a broken NW. slope.
29.66	The ½ sec. cor. of sec. 6, only, hereinafter described. Descend 80 ft. over a broken NW. slope.
44.44	The standard ½ sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	S. 89° 50' W., beginning new measurement, along the S. bdy. of sec. 31.
	Descend 240 ft. over a broken steep NW. slope.
10.80	Ravine, course NW.; continue to descend 110 ft. over a broken NW. slope.
21.90	Buffalo Canyon, 2½ chs. wide, course S. 60° W.; asc. a gradual SE. slope.
22.69	The closing corner of T. 15 N., Rs. 37 and 38 E., hereinafter described.
23.20	Track road, bears N. 60° E. and S. 60° W.; asc. 130 ft. over a SSE. slope.
36.67	Angle point bet. secs. 1 and 31, determined by the stump hole of a dead pinon tree, 7 ins. diam., lying on the ground and mkd. AP.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	T16N R38E A P <u>S31</u> S 1 T 15N R37E 1963