## DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH

	***	DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH THROUGH RANGE 38 EAST, MDM., NEVADA
	CHAINS	WEST, beginning new measurement, along the S. bdy. of sec. 31.
	0.60	Small spur, slopes S.; desc. 50 ft. over a W. slope.
	3.38	The standard cor. of T. 16 N., Rs. 37 and 38 E., monumented with an iron post, 3 ins. diam., mkd. set and witnessed as described in the official record.
		Land, mountainous. Soil, rocky and sandy loam. Timber, juniper and pinon pine'
		DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 15 N., R. 38 E., MDM., NEVADA
		Re-establishment of the survey executed by Stewart and Morrison, Deputy Surveyors, in 1883.
		The cor. of Tps. 14 and 15 N., Rs. 38 and 39 E., monumented with a granite stone, 15x12x10 ins., plainly mkd. and firmly set.
		At the corner point
	•	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
		T15N R38E R39E S 36   S 31 S 1   S 6 T14N 1963
_		bury the original cornerstone alongside the iron post.
		N. 89° 20' W., bet. secs. 1 and 36.
		Over low rolling land covered with scrub sage and salt brush.
		Descend 50 ft. over a gentle W. slope.
	40.52	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
The second secon		T15N R38E  2 S 36 S 1 T14N 1963
١		

Descend 40 ft. over a gentle W. slope.