

DEPENDENT RESURVEY, W. BDY., T. 15 N., R. 38 E.

CHAINS

DEPENDENT RESURVEY, W. BDY., T. 15 N., R. 38 E.

Re-establishment of the survey executed by Stewart and Morrison, Deputy Surveyors, in 1883.

From the cor. of secs. 1, 6, 31 and 36, Tps. 14 and 15 N., Rs. 37 and 38 E., heretofore described.

N. 0° 17' W., bet. secs. 31 and 36.

Over nearly level land covered with sage and salt brush.

35.00 Bladed road, bears NE. and SW.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T15N
R37E R38E
 $\frac{1}{4}$
S 36 | S 31
1963

80.13 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T15N
R37E R38E
S 25 | S 30
S 36 | S 31
1963

Land, nearly level.
Soil, sandy clay.
Undergrowth, sage and salt brush.

N. 0° 17' W., bet. secs. 25 and 30.

Over low rolling land covered with sage and salt brush; asc. 30 ft. over a gentle S. slope.

16.80 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 30 ft. over a gentle S. slope.

40.07 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a granite stone, 10x8x6 ins., plainly mkd and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T15N
R37E R38E
 $\frac{1}{4}$
S 25 | S 30
1963

bury the original cornerstone alongside the iron post.