

DEPENDENT RESURVEY, T. 15 N., R. 38 E.

CHAINS

N. 4° 10' E., bet. secs. 1 and 2.

Over rolling land covered with sage and salt brush.

Descend 20 ft. over a broken NE. slope.

39.68 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T15N R38E

$\frac{1}{4}$
S 2 | S 1
1963

continue over low rolling land covered with sage.

79.13 Intersect the Third Standard Parallel North.

Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T16N R38E

S 36
S 2 | S 1
CC
T15N
1963

from which

The standard cor. of secs. 35 and 36, T. 16 N., R. 38 E., heretofore described, bears S. 89° 33' W., 10.06 chs. dist.

The angle point on the S. bdy. of sec. 36, T. 16 N., R. 38 E., heretofore described, bears N. 89° 33' E., 29.83 chs. dist.

Land, rolling.

Soil, sandy clay.

Undergrowth, sage and salt brush.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 at midpoint and on the N. bdy. of the Tp.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

$\frac{1}{4}$ S 1
T15N R38E
1963