

DEPENDENT RESURVEY, T. 15 N., R. 38 E.

CHAINS

30.00

Spur, slopes SE.; desc. 80 ft. over a NE. slope.

39.57

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T15N R38E

	$\frac{1}{4}$	
S 3		S 2
1963		

Descend 110 ft. over a NE. slope.

78.83

Intersect the Third Standard Parallel North.

Point for the closing corner of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T16N R38E

	S 35	
S 3		S 2
CC		
T15N		
1963		

from which

The standard corner of secs. 34 and 35, T. 16 N., R. 38 E., heretofore described, bears S. $89^{\circ} 33'$ W., 9.67 chs. dist.

The angle point on the S. bdy. of sec. 35, T. 16 N., R. 38 E., heretofore described, bears N. $89^{\circ} 33'$ E., 29.55 chs. dist.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper and pinon.

Undergrowth, sage and salt brush.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 at midpoint and on the N. bdy. of the Tp.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

	$\frac{1}{4}$	S 2
T15N		R38E
1963		

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 16 N., R. 38 E., heretofore described, bears S. $89^{\circ} 33'$ W., 9.88 chs. dist.