

## DEPENDENT RESURVEY, T. 15 N., R. 38 E.

## CHAINS

- 5.20 Bladed road, bears NE. and SW.; asc. 50 ft. over a SE. slope.
- 12.20 Unimproved road, bears E. and W.; asc. 260 ft. over a SE. slope.
- 34.10 Spur, slopes E.; desc. 100 ft. over a NE. slope.
- 40.18 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.; 22 ins. in the ground, with brass cap mkd.

T15N R38E

$\frac{1}{4}$   
S 5 | S 4  
1963

from which

A pinon, 5 ins. diam., bears N.  $56^\circ$  E., 41 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

Descend 30 ft. over a NE. slope.

- 41.80 Jeep road in bottom of draw, drains SE.; asc. 200 ft. over a broken S. slope.
- 80.03 Intersect the Third Standard Parallel North.

Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground and in a mound of stone,  $3\frac{1}{2}$  ft. base to top, with brass cap mkd.

T16N R38E

S 33  
S 5 | S 4  
CC  
T15N  
1963

from which

The angle point on the S. bdy. of sec. 33, T. 16 N., R. 38 E., heretofore described, bears N.  $89^\circ 39'$  W., 10.82 chs. dist.

The standard  $\frac{1}{4}$  sec. cor. of sec. 33, T. 16 N., R. 38 E., heretofore described, bears S.  $89^\circ 39'$  E., 22.25 chs. dist.

Land, rolling.

Soil, sandy clay.

Timber, medium dense pinon and juniper.

Undergrowth, sage, bitter brush and bunchgrass.