

DEPENDENT RESURVEY OF THE EAST BDY., T. 17 N., R. 39 E.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R39E R40E ½ S 12 S 7 1963</p>
	<p>bury the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 13' E., beginning new measurement.</p>
37.00	<p>Improved dirt road, bears ESE. and WNW.</p>
40.12	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a trapstone, 16x12x10 ins., plainly mkd. and firmly set.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R39E R40E S 1 S 6 S 12 S 7 1963</p>
	<p>deposit broken glass around iron post and bury the original cornerstone alongside the iron post.</p> <p>Land, low rolling. Soil, sandy loam. Undergrowth, sage and salt brush.</p>
	<p>N. 0° 37' W., bet. secs. 1 and 6.</p> <p>Over low rolling land covered with dense sage and salt brush.</p>
7.70	<p>Dry wash, 50 lks. wide, 2 ft. deep, drains SE.</p>
40.15	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R39E R40E ½ S 1 S 6 1963</p>
	<p>deposit broken glass around the iron post.</p>
80.31	<p>The cor. of Tps. 17 and 18 N., Rs. 39 and 40 E., monumented with a squared stake badly deteriorated, loosely set in a mound of earth.</p>