

DEPENDENT RESURVEY OF THE SOUTH BDY., T. 18 N., R. 39 E.

CHAINS

T18N R39E

S 31 | S 32

S 6

T17N

1963

Land, high rolling.
 Soil, sandy clay and stony.
 Timber, scattered pinon and juniper.
 Undergrowth, sagebrush, salt brush and grass.

S. 88° 59' W., along the S. bdy. of sec. 31.

Over high rolling land covered with scattered timber.

Ascend 120 ft. over an E. slope.

9.50 Ridge, bears N. and S.; desc. 70 ft. over a W. slope.

32.10 Unimproved road, bears N. and S.

32.40 Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. 30 ft. over a W. slope.

36.50 The $\frac{1}{4}$ sec. cor. of sec. 6 only, hereinafter described; asc. 20 ft. over a W. slope.39.25 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the $\frac{1}{4}$ sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T18N R39E

 $\frac{1}{4}$ S 31

T17N

1963

Ascend 490 ft. over an E. slope.

66.10 Ridge, bears N. and S.; desc. 300 ft. over a W. slope.

76.48 The closing cor. of Tps. 17 N., Rs. 38 and 39 E., hereinafter described; desc. 70 ft. over a W. slope.

78.50 The cor. of Tps. 17 and 18 N., Rs. 38 and 39 E., monumented with a granite stone, 18x12x10 ins., plainly mkd. and firmly set. This cor. now refers to Tps. 18 N., Rs. 38 and 39 E.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T18N

R38E R39E

S 36 | S 31

S 1

T17N R38E

1963

bury the original cornerstone alongside the iron post.