

DEPENDENT RESURVEY OF THE N. BDY. OF T. 28 N., R. 61 E.

CHAINS

36.80 Wash, 10 lks. wide, 2 ft. deep, drains NE.

39.84 Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone with brass cap mkd.

T29N R61E
 1/4 S 32
 S 5
 T28N
 1963

58.00 Wash, 10 lks. wide, 1 ft. deep, drains N.

68.00 Wash, 10 lks. wide, 1 ft. deep, drains N.

79.68 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone with brass cap mkd.

T29N R61E
 S 31 | S 32
 S 6 | S 5
 T28N
 1963

Land, rolling.
 Soil, gravelly loam.
 Timber, none; undergrowth, sagebrush and greasewood.

N. 88° 09' W., bet. secs. 6 and 31.

Over rolling land.

15.00 Trail road, bears NE. and SW.

39.84 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T29N R61E
 1/4 S 31
 S 6
 T28N
 1963

78.93 The cor. of Tps. 28 and 29 N., Rs. 60 and 61 E., monumented with a wooden post, 3x3x20 ins., dimly mkd., loosely set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.