

Dependent Resurvey of the N. Bdy. of T. 27 N., R. 62 E.

CHAINS

N. 87° 46' W., bet. secs. 5 and 32.

Over rolling land; desc. a gradual W. slope.

39.70 The 1/4 sec. cor. of secs. 5 and 32, monumented with a wooden post, 1x1x24 ins., dimly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

T28N R62E

1/4 S 32
S 5

T27N

1963

bury the original corner alongside the iron post.

No accessories available.

S. 89° 09' W., beginning new measurement.

Desc. a rolling W. slope.

39.90 The cor. of secs. 5, 6, 31 and 32, monumented with a wooden post, 2x2x36 ins., plainly mkd. and loosely set

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone with brass cap mkd.

T28N R62E

S 31 | S 32
S 6 | S 5

T27N

1963

bury the original corner alongside the iron post.

Land, rolling.

Soil, clay loam.

Timber, none.

Undergrowth, sagebrush and bunchgrass.

N. 89° 38' W., bet. secs. 6 and 31.

Over rolling land; desc. a gentle W. slope.

16.00 Irrigation ditch, flows SW.

40.00 The 1/4 sec. cor. of secs. 6 and 31, monumented with a wooden post, 1x1x20 ins., dimly mkd. and loosely set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground and in a collar of stone with brass cap mkd.

T28N R62E

1/4 S 31
S 6

T27N

1963