

Dependent Resurvey of the W. Bdy. of T. 27 N., R. 62 E.

CHAINS

Dependent Resurvey of the W. Bdy. of T. 27 N., R. 62 E.,
Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by Preble
and Thorburn, Deputy Surveyors in 1881.

From the cor. of Tps. 26 and 27 N., Rs. 61 and 62 E.
N. 0° 15' E., bet. secs. 31 and 36.

Over rolling land.

40.45 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in
the ground and in a collar of stone, with brass cap mkd.

T27N
R61E R62E
 $\frac{1}{4}$
S 36 | S 31
1963

54.60 Wash, 10 lks. wide, 2 ft. deep, drains SE.

73.00 Enter timber, bears NW. and SE.

80.90 The cor. of secs. 25, 30, 31 and 36, monumented with a
wooden post, 2x2x24 ins., dimly mkd. and loosely set.

At the corner point:

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in
the ground to bedrock and in a mound of stone, $3\frac{1}{2}$ ft.
base to top, with brass cap mkd.

T27N
R61E R62E
S 25 | S 30
S 36 | S 31
1963

bury the original corner alongside the iron post.

Land, rolling.

Soil, clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush and bunchgrass.

N. 0° 40' E., bet. secs. 25 and 30.

Over rolling land, through timber.

21.60 Bladed road, bears E. and W.

39.89 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground and in a collar of stone, with brass cap mkd.