

Survey of Subdivisional Lines of T. 19 N.,  
R. 48 E., MDM., Nevada

CHAINS	
	WEST, bet. secs. 30 and 31.  Over low rolling land covered with sage.
5.80	Small wash, drains N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T19N R48E $\frac{1}{4} \begin{array}{ c c }\hline S & 30 \\ \hline S & 31 \\ \hline \end{array}$ 1964 raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.
44.60	Improved dirt road, bears N. and S.
77.48	The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., set, mkd., and witnessed as described in the field notes of the survey of T. 19 N., R. 47 E.  Land, gentle rolling. Soil, sandy clay loam. Undergrowth, sagebrush.
	From the cor. of secs. 29, 30, 31 and 32.  N. $0^\circ 03'$ W., bet. secs. 29 and 30.  Over gentle rolling land covered with sage.
9.00	Small wash, drains NNW.
28.40	U. S. Highway No. 50 bears N. $77^\circ 06'$ E. and S. $77^\circ 06'$ W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T19N R48E $\frac{1}{4} \begin{array}{ c c }\hline S & 30 \\ \hline S & 29 \\ \hline \end{array}$ 1964 raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high W. of corner.
65.20	Small wash, drains NNW.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T19N R48E $\frac{1}{4} \begin{array}{ c c }\hline S & 19 \\ \hline S & 20 \\ \hline \end{array}$ 1964