

DEPENDENT RESURVEY, N. BDY., T. 16 N., R. 47 E.

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T17N R47E
S 32
 S 6 | S 5
 T16N
 1964

bury the original cornerstone alongside the iron post.

Land, nearly level.

Soil, sandy clay loam.

Undergrowth, sagebrush and bunchgrass.

N. 88° 59' W., on the N. bdy. of sec. 6.

Over gentle rolling land, covered with sage.

3.95 Point for the cor. of secs. 31 and 32, T. 17 N., R. 47 E., 80.00 chains in departure from the cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R47E
S 31 | S 32
 S 6
 T16N
 1964

raise a mound of stone, 2½ ft. base, 18 ins. high, N. of corner.

Asc. 50 ft. over an E. slope.

39.54 The ¼ sec. cor. of secs. 6 and 31, monumented with a limestone, 13x11x9 ins., firmly set in a mound of stone and plainly mkd. with ¼ on the N. face. This cor. will now refer to the ¼ sec. of sec. 6 only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T17N R47E
¼ S 6
 T16N
 1964

bury the original cornerstone alongside the iron post.

N. 89° 01' W., beginning new measurement.