

SURVEY OF THE SUBDIVISIONAL LINES OF T. 17 N., R. 47 E.

CHAINS

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T17N R47E
 $\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$
 1964
- raise a mound of stone, $2\frac{1}{2}$ ft. base, 18 ins. high, N. of corner.
- 48.00 Leave nearly level valley and enter gentle rolling land; ascend 40 ft. over an E. slope.
- 56.00 Spur, slopes NE.; desc. 20 ft. over a W. slope.
- 64.00 Draw, drains NE., asc. 40 ft. over an E. slope.
- 80.00 Point for the cor. of secs. 29, 30, 31 and 32, at the intersection with the fifth meridional line.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T17N R47E
 $\frac{S\ 30}{S\ 31}$ | $\frac{S\ 29}{S\ 32}$
 1964
- raise a mound of stone, $2\frac{1}{2}$ ft. base, 18 ins. high, W. of corner.
- Land, nearly level to rolling.
 Soil, sandy clay and light gravel.
 Undergrowth, sagebrush and shadscale.
-
- WEST, bet. secs. 30 and 31, on the sectional correction line.
- Over gentle rolling land, covered with sagebrush; asc. 20 ft. over an E. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T17N R47E
 $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$
 1964
- raise a mound of stone, $2\frac{1}{2}$ ft. base, 18 ins. high, N. of corner.
- Asc. 80 ft. over an E. slope.
- 75.14 Intersect the E. bdy. of T. 17 N., R. 46 E.