

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 47 E.

CHAINS

75.04

Intersect the E. bdy. of T. 17 N., R. 46 E.

Point for the closing corner of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a collar of stone with brass cap mkd.

T17N	
R46E	R47E
S 25	S 19 C
	S 30 C
1964	

from which

The cor. of secs. 24 and 25, T. 17 N., R. 46 E., heretofore described, bears NORTH, 8.75 chains distance.

Land, rolling.

Soil, sandy clay and light gravel.

Undergrowth, sagebrush and shadscale.

Point for the W. ¼ sec. cor. of sec. 30, at midpoint and on the E. bdy. of T. 17 N., R. 46 E.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N	
R46E	R47E
	¼
	S 30
1964	

raise a mound of stone, 2½ ft. base, 18 ins. high, E. of corner.

from which

The ¼ sec. cor. of sec. 25, T. 17 N., R. 46 E., heretofore described, bears NORTH, 8.75 chains distance.

From the corner of secs. 19, 20, 29 and 30.

N. 0° 03' W., bet. secs. 19 and 20.

Over gentle rolling land, through medium dense undergrowth.

24.60

Small wash, drains ENE.

40.00

Point for the ¼ sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N	R47E
	¼
S 19	S 20
1964	