

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 47 E.

CHAINS	40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div><div>T17N R47E</div><div>$\frac{1}{4}$ <div>S 18</div><div>S 19</div></div><div>1964</div></div> <p>Asc. 50 ft. over an E. slope.</p>
	74.86	<p>Intersect the E. bdy. of T. 17 N., R. 46 E.</p> <p>Point for the closing corner of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. dia., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div><div>T17N</div><div>R46E R47E</div><div>S 24 <div>S 18 C</div><div>S 19 C</div></div><div>1964</div></div> <p>from which</p> <p>The cor. of secs. 13 and 24, T. 17 N., R. 46 E., heretofore described, bears NORTH, 8.76 chains distance.</p> <p>Land, gentle rolling. Soil, sandy clay and light gravel. Undergrowth, sagebrush and shadscale.</p>
		<p>Point for the W. $\frac{1}{4}$ sec. cor. of sec. 19, is at midpoint and on the E. bdy. of T. 17 N., R. 46 E.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T17N</div><div>R46E R47E</div><div>$\frac{1}{4}$ </div><div>S 19</div><div>1964</div></div> <p>raise a mound of stone, $2\frac{1}{2}$ ft. base, 18 ins. high, E. of corner.</p> <p>from which</p> <p>The $\frac{1}{4}$ sec. cor. of sec. 24, T. 17 N., R. 46 E., heretofore described, bears NORTH, 8.76 chains distance.</p>
		<p>From the corner of secs. 17, 18, 19 and 20.</p> <p>N. $0^{\circ} 03'$ W., bet. secs. 17 and 18.</p>