

106

SURVEY OF THE E. BDY., T. 18 $\frac{1}{2}$ N., R. 46 E.

CHAINS

T18 $\frac{1}{2}$ N
R46E | R47E
 $\frac{1}{4}$ |
S 12 |
1964

Desc. 30 ft. over a broken NE. slope.

- 48.30 Base of sandstone ledge, 10 ft. high, bears NE. and SW.; asc. 110 ft. over a S. slope.
- 56.30 Spur, slopes SW.; desc. 230 ft. over a N. slope.
- 71.23 The closing cor. of secs. 6 and 7, T. 18 $\frac{1}{2}$ N., R. 47 E., hereinafter described.
- 80.00 Point for the cor. of secs. 1 and 12, T. 18 $\frac{1}{2}$ N., R. 46 E.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T18 $\frac{1}{2}$ N
R46E | R47E
S 1 | S 6
S 12 |
1964

Cor. falls in bottom of small draw, draining NE.

Land, high rolling.

Soil, sandy clay and stony.

Undergrowth, sagebrush, shadscale and scattered bunch grass.

NORTH, on the E. bdy. of sec. 1.

Over low rolling land, covered with sage; desc. 90 ft. over a N. slope.

- 20.80 Wash, 10 lks. wide, 3 ft. deep, drains NE.; desc. 50 ft. over a N. slope.
- 28.50 U. S. Highway No. 50, bears NE. and SW.
- 31.23 The $\frac{1}{4}$ sec. cor. of sec. 6, only, T. 18 $\frac{1}{2}$ N., R. 47 E., hereinafter described.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 1, T. 18 $\frac{1}{2}$ N., R. 46 E.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T18 $\frac{1}{2}$ N
R46E | R47E
 $\frac{1}{4}$ |
S 1 |
1964

- 45.48 Intersect the S. bdy. of T. 19 N., R. 47 E.
- Point for the closing corner of T. 18 $\frac{1}{2}$ N., Rs. 46 and 47 E.