

SUBDIVISION OF T. 18½ N., R. 47 E.

CHAINS	
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.</p> <p>Land, low rolling. Soil, sandy clay and light gravel. Undergrowth, sagebrush and sparse bunchgrass.</p>
39.99	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 57' W., bet. secs. 5 and 8.</p> <p>Over nearly level land, covered with sage.</p> <p>Point for the ¼ sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18½N R47E</p> <p>¼ S 5</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 8</p> <p>1964</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of the iron post.</p>
65.60	Graded road, bears N. 10° W., and S. 10° E.
79.98	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>from which</p> <p style="padding-left: 40px;">A windmill and well, bears S. 35° 49' E., 19.67 chains dist.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush.</p>
22.70	<p>WEST, bet. secs. 6 and 7.</p> <p>Over rolling land, covered with crested wheat; asc. 60 ft. over an E. slope.</p> <p>Leave reseeding area; asc. 30 ft. over a NE. slope.</p>
27.60	Spur, slopes N.; asc. 10 ft. along a broken NE. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18½N R47E</p> <p>¼ S 6</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 7</p> <p>1964</p> </div> <p>Asc. 30 ft. over a broken N. slope.</p>
73.75	<p>Intersect the E. bdy. of T. 18½ N., R. 46 E.</p> <p>Point for the closing corner of secs. 6 and 7.</p>