

## SUBDIVISION OF T. 18½ N., R. 47 E.

CHAINS

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 03' W., bet. secs. 5 and 6.

Over low, rolling land, covered with sage.

40.00 Point for the ¼ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18½N R47E

¼	
S 6	S 5
1964	

54.14 Intersect the S. bdy. of T. 19 N., R. 47 E.

Point for the closing corner of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T19N R47E

S 32	
S 6	S 5
C	C
T18½N	
1964	

raise a mound of stone, 3 ft. base, 2 ft. high, S. of corner.

from which

The ¼ sec. cor. of sec. 32, T. 19 N., R. 47 E., bears EAST, 10.72 chains dist., monumented with an iron post, 1 inch diam., set, mkd. and witnessed as described in the field notes of the official survey of T. 19 N., R. 47 E.

The cor. of secs. 31 and 32, T. 19 N., R. 47 E., bears WEST, 29.28 chains dist., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the official survey of T. 19 N., R. 47 E.

Land, gently rolling.

Soil, sandy clay and light gravel.

Undergrowth, sagebrush.

The N. ¼ sec. cor. of sec. 5, at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T19N R47E

¼	S 5
---	-----

T18½N R47E  
1964