SURVEY OF SUBDIVISIONAL LINES OF T. 21 N., R. 49 E., MDM., NEVADA

	T. 21 N., R. 49 E., MDM., NEVADA
CHAINS	From the standard corner of secs. 34 and 35 on the S. bdy of the Tp., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the survey of the Fourth Standard Parallel North, through Range 49 East.
	N. 0° 03' W., bet. secs. 34 and 35.
	Over nearly level land, through medium undergrowth.
40.00	Point for the & sec. cor. of secs. 34 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T21N R49E
	s 34 s 35 1964
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
62,40	Trail road, bears N. 52° 30' E. and S. 52° 30' W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T21N R49E <u>S 27 S 26</u> S 34 S 35 1964
7	raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
	Land, nearly level. Soil, sandy clay and light gravel. Undergrowth, sagebrush.
	From the cor. of secs. 25, 26, 35 and 36.
one one is a some of the	S. 89° 55' W., bet. secs. 26 and 35.
* ·	Over nearly level land, through medium undergrowth.
40.00	Point for the 2 sec. cor. of secs. 26 and 35.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T21N R49E
	S 26 S 35 1964
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.
59.60	Trail road, bears NE. and SW.
80.00	The cor. of secs. 26, 27, 34 and 35.