

SUBDIVISION OF T. 20 N., R. 48 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R48E
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{1}{12}$
 1964

raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

65.50 Leave nearly level valley, and asc. 30 ft. over a SE. slope.

76.50 Spur, slopes NE.; desc. 30 ft. over a NW. slope.

80.00 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.
 Soil, sandy clay.
 Undergrowth, sagebrush.

N. $0^{\circ} 01'$ W., bet. secs. 1 and 2.

Over gentle rolling land, through medium undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R48E
 $\frac{1}{4}$
 S 2 S 1
 1964

raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

64.00 Irrigation ditch, drains SE.

67.00 Wash, drains SE.

81.13 Intersect the Fourth Standard Parallel North.

Point for the closing corner of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R48E
 S 36
 S 2 S 1
 C C
 T20N
 1964

raise a mound of stone, 3 ft. base, 2 ft. high, S. of corner.

from which