## SUBDIVISION OF T. 20 N., R. 48 E

SUBDIVISION OF T. 20 N., R. 48 E.
Point for the ½ sec. cor. of secs. 3 and 10.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
120N R48E  2 S 3 S 10
1964
raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.
from which
A windmill and well, bears S. 20° 25' W., 44.68 chs. dist.
Rocky spur, slopes S., 3.00 chains distance to end; desc. 30 ft. over a W. slope.
Improved road, bears NW. and SE., 3.00 chains distance, thence N. 80° E.
The cor. of secs. 3, 4, 9 and 10.
Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush.
N. 0° 02' W., bet. secs. 3 and 4.
Over rolling land, through medium undergrowth.
Improved road, bears SE. and NW., 1.00 chain distance, thence W.; asc. 20 ft. over a SE. slope.
Trail road, bears SW. and NE.; asc. 240 ft. over a SE. slope.
Crest of rocky spur, slopes E.; desc. 40 ft. over a N. slope.
Point for the ½ sec. cor. of secs. 3 and 4.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
T20N R48E  \$ 5 4   S 3  1964
Desc. 10 ft. over a N. slope.
Slope changes to W.; desc. 210 ft.
Wash, 10 lks. wide, 12 ins. deep, drains N. 10° E.
Intersect the Fourth Standard Parallel North.