

## SUBDIVISION OF T. 20 N., R. 48 E.

## CHAINS

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 53' W., bet. secs. 4 and 9.

Over rolling land, through medium undergrowth; asc. 70 ft. over an E. slope.

40.02 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T20N R48E  
 $\frac{1}{4}$  S 4  
 S 9  
 1964

Asc. 80 ft. over an E. slope.

70.40 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft. over a SE. slope.

80.04 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, stony.

Undergrowth, sagebrush and cheat grass.

N. 0° 03' W., bet. secs. 4 and 5.

Over rolling land, through medium undergrowth; asc. 30 ft. along a SE. slope.

10.90 Wash, 20 lks. wide, 3 ft. deep, drains SE.; asc. 30 ft. along an E. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., on bed-rock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T20N R48E  
 $\frac{1}{4}$   
 S 5 S 4  
 1964

Asc. 60 ft. over a broken E. slope.

80.77 Intersect the Fourth Standard Parallel North.

Point for the closing corner of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R48E  
 S 33  
 S 5 S 4  
 C C  
 T20N  
 1964