

## SUBDIVISION OF T. 20 N., R. 48 E.

## CHAINS

- 22.00 Wash, 10 lks. wide, 2 ft. deep, drains SE.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
- T20N R48E  
 $\frac{1}{4}$  S 30  
S 31  
1964
- raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.
- 55.70 Wash, 10 lks. wide, 2 ft. deep, drains ESE.
- 77.47 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the survey of T. 20 N., R. 47 E.
- Land, gentle rolling.  
Soil, sandy clay loam.  
Undergrowth, sagebrush.
- 
- From the cor. of secs. 29, 30, 31 and 32.  
N.  $0^{\circ} 03'$  W., bet. secs. 29 and 30.  
Over mountainous land, through medium undergrowth; asc. 30 ft. over a broken SW. slope.
- 16.00 Top of spur, slopes NW.; desc. 30 ft. over a N. slope.
- 28.00 Small wash, drains NW., 5.00 chains distance, thence SW.; asc. 20 ft. along a SW. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
- T20N R48E  
 $\frac{1}{4}$   
S 30 | S 29  
1964
- raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
- 46.20 Small wash, drains SW.; asc. 340 ft. over a SW. slope.
- 76.00 Spur, slopes SE.; desc. 10 ft. over a NE. slope.
- 80.00 Point for the cor. of secs. 19, 20, 29 and 30.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone,  $3\frac{1}{2}$  ft. base to top, with brass cap mkd.