

## SUBDIVISION OF T. 20 N., R. 48 E.

## CHAINS

Asc. 230 ft. over a SE. slope.

51.80 Spur, slopes E.; desc. 270 ft. over a steep broken N. slope.

60.10 Bottom of canyon, small stream of water, 12 ins. wide, 2 ins. deep, drains E.; asc. 210 ft. over a S. slope.

72.50 Spur, slopes SE.; desc. 20 ft. over an E. slope.

80.64 Intersect the Fourth Standard Parallel North.

Point for the closing corner of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone,  $3\frac{1}{2}$  ft. base to top, with brass cap mkd.

T21N. R48E

S	32
S 6	S 5
C	C
T20N	
1964	

from which

The standard  $\frac{1}{4}$  sec. cor. of sec. 32, T. 21 N., R. 48 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears EAST, 10.95 chs. dist.

The standard cor. of secs. 31 and 32, T. 21 N., R. 48 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record, bears WEST, 29.05 chs. dist.

Land, mountainous.

Soil, stony and sandy.

Undergrowth, sagebrush and bunch grass.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5 is at mid-point, and on the N. bdy. of the Tp.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T21N. R48E

$\frac{1}{4}$ S	5
T20N R48E	
1964	

from which

The standard cor. of secs. 32 and 33, T. 21 N., R. 48 E., heretofore described, bears EAST, 10.92 chs. dist.

The standard  $\frac{1}{4}$  sec. cor. of sec. 32, T. 21 N., R. 48 E., heretofore described, bears WEST, 29.08 chs. dist.