

DEPENDENT RESURVEY, S. BDY., T. 12 N., R. 64 E.

CHAINS

Reestablishment of the Survey Executed by E. B. Monroe and A. G. Bateman, Deputy Surveyors, in 1874.

Point for the corner of Tps. 11 and 12, N., Rs. 64 and 65 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N	
R64E	R65E
S 36	S 31
S 1	S 6
T11N	

1964

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

from this corner

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, Tps. 11 and 12 N., R. 66 E., monumented with a squared wooden post, 3x3x24 ins., set and marked as described in the official record, bears N. $89^{\circ} 26' E.$, 919.99 chs. dist. **This control line was**

retraced and search made for evidence of intervening corners, none were found.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N R66E	
$\frac{1}{4}$	S 36
S 1	
T11N	
1964	

reset the corner post alongside the iron post and raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, T. 11 N., Rs. 64 and 65 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the dependent resurvey of the exterior lines of T. 11 N., R. 64 E., executed concurrently under this same group, bears S. $0^{\circ} 07' W.$, 439.34 chs. dist.

S. $89^{\circ} 23' W.$, bet. secs. 1 and 36.

Over rolling mountainous land, draining generally SW.

40.04

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.