

DEPENDENT RESURVEY, S. BDY., T. 12 N., R. 64 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N	R64E
¼	S 32
<hr/>	
	S 5
	T11N

1964

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

49.00 Wash, drains irregularly NNE.

80.08 The cor. of secs. 5, 6, 31 and 32, monumented with a porphyry stone, 8x10x14 ins., firmly set, mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T12N	R64E
S 31	S 32
<hr/>	
S 6	S 5
	T11N

1964

reset the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly clay loam.
Timber, scattered juniper and pinon.
Undergrowth, sagebrush.

N. 87° 05' W., bet. secs. 6 and 31.

Over rolling land, through scattered timber.

10.00 Graded road, bears NNE. and SSW.

38.76 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N	R64E
¼	S 31
<hr/>	
	S 6
	T11N

1964