

DEPENDENT RESURVEY, W. BDY., T. 12 N., R. 64 E.

CHAINS

40.04

Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T12N
R63E R64E
 $\frac{1}{4}$
S 12 | S 7

1964

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Over a broken E. slope.

80.08

The cor. of secs. 1, 6, 7 and 12, monumented with a wooden post, 3 ins. diam., 20 ins. long, set and marked as described in the official record.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T12N
R63E R64E
S 1 | S 6
S 12 | S 7

1964

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, pinon and juniper.

Undergrowth, sagebrush and rabbit brush.

N. $0^{\circ} 08'$ W., bet. secs. 1 and 6.

Over rolling mountainous land, asc. 400 ft. over a SW. slope.

34.00

Top of spur, slopes E.; desc. 130 ft. over a N. slope.

39.96

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with an unmarked porphyry stone, 14x10x8 ins. firmly set in the ground and in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to cap, with brass cap mkd.