DEPENDENT	RESURVEY.	Τ.	12	Ν	R.	64	Ε.

=-,							
	CHAINS	N. 0° 57' E., bet. secs. 2 and 3.					
		Over rolling land, draining northwesterly; desc. 100 ft. over a WNW. slope.					
	30.00	Trail road in ravine, draining NW.; over rolling land.					
	40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.					
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.					
		T12N R64E					
		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$					
		1965					
		raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.					
		Over rolling land, draining northwesterly.					
1	80.05	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the dependent resurvey of the S. bdy., T. 13 N., R. 64 E., executed concurrently under this same group.					
***************************************		Land, rolling. Soil, sandy and gravelly clay loam. Timber, pinon and juniper. Undergrowth, sagebrush.					
		From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.					
		N. 0° 04' W., bet. secs. 33 and 34.					
		Over rolling land, draining westerly.					
	40.07	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.					
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to cap, with brass cap mkd.					
		T12N_ R64E					
		S 33 S 34					
		1965					