DEPENDENT	RESURVEY.	Τ.	12	Ν.,	R.	64	Ε.

	DEPENDENT RESURVEY, T. 12 N., R. 64 E.				
CHAINS					
,	Land, rolling.				
	Soil, sandy and gravelly clay loam. Timber, pinon and juniper.				
	Undergrowth, sagebrush and crested wheat.				
	N. 0° 03' W., bet. secs. 4 and 5.				
	Over nearly level land.				
17.20	Fence, bears E. and W.				
19.20	Road, bears E. and W.				
40.20	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.				
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.				
	T12N R64E				
	S 5 S 4				
,	1965				
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.				
80.15	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the dependent resurvey of the S. bdy., T. 13 N., R. 64 E., executed concurrently under this same group.				
	Land, nearly level.				
	Soil, sandy and gravelly clay loam. Timber, none.				
	Undergrowth, sagebrush and crested wheat.				
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.				
	N. 0° 01' E., bet. secs. 31 and 32.				
	Over gently rolling land, through scattering timber and undergrowth.				
40.70	The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a porphyry stone, $18x14x10$ ins. firmly set in the ground and plainly mkd. $\frac{1}{4}$ on the W. face.				
	At the corner point				
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.				