

DEPENDENT RESURVEY, T. 13 N., R. 64 E.

CHAINS	
26.60	Trail road, bears NW. and SE.
40.20	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T13N R64E} \\ \text{S } 1 \\ \hline \frac{1}{4} \text{ S } 12 \end{array}$ <p>1964</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>From this corner station WPA 081, of the Nevada Planning Dept. of the Nevada Highway Dept., a T bar steel fence post, mkd. WPA 081, bears N. $33^{\circ} 17' W.$, 14.48 chs. dist.</p>
80.40	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy, clay and gravel. Timber, juniper and pinon.</p>
	<p>N. $0^{\circ} 14' E.$, bet. secs. 1 and 2.</p> <p>Over nearly level land, through scattered undergrowth.</p>
25.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.
28.00	Road, gravel, bears NE. and SW.
28.50	Fence, bears NE. and SW.; enter reseeded area.
40.54	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T13N R64E} \\ \text{S } 2 \mid \text{S } 1 \\ \hline \frac{1}{4} \end{array}$ <p>1964</p> <p>raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p>
68.40	Trail road, bears NE. and SW.
77.80	Fence, bears E. and W. Leave reseeded area.
81.03	The cor. of secs. 1, 2, 35 and 36, Tps. 13 and 14 N., R. 64 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 14 N., R. 64 E.