

DEPENDENT RESURVEY, E. BDY. T. 14 N., R. 64 E.

CHAINS	
47.40	Top of ascent slopes W.; continue over gently rolling land.
70.70	Trail road, bears ENE. and WSW.
79.90	Fence, bears E. and W. 1.22 chs. distance; thence N.
81.88	The cor. of secs. 1, 6, 7 and 12, monumented with a mound of stone, which is accepted as the best remaining evidence of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T14N R64E R65E S 1 S 6 S 12 S 7</p>
	1964
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<p>Land, rolling. Soil, sandy gravel. Undergrowth, sagebrush, Timber, scattered juniper.</p>
	N. 1° 08' W., bet. secs. 1 and 6.
	Over gently rolling land, through medium undergrowth, along a fence.
7.80	Trail road, bears E. and W.
28.60	Trail road, bears SE. and NW.
38.00	Trail road, bears SE. and NW.
40.50	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T14N R64E R65E ¼ S 1 S 6</p>
	1964
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
61.00	Fence, bears N. 1° E. and S. 1° W.
81.00	Point for the cor. of Tps. 14 and 15 N., Rs. 64 and 65 E. at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in