

COMPLETION SURVEY OF T. 40 N., R. 40 E.

CHAINS

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 3.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | |
|------|---------------|
| T40N | R40E |
| | $\frac{1}{4}$ |
| | S 3 |
| | 1965 |
- raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
- 40.90 Small wash, drains WNW.
- 42.67 Point for the E. $\frac{1}{4}$ sec. cor. of sec. 4, at 40.00 chs. in latitude from the closing cor. of secs. 4 and 9.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | |
|---------------|------|
| T40N | R40E |
| $\frac{1}{4}$ | |
| S 4 | |
| | 1965 |
- raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- From this corner, U.S.G.S. Bench Mark T-20, bears N. 85° 59' W., 56.03 chs. dist.
- 63.60 Bladed dirt road, bears ESE. and NW.
- 66.80 Wash, 10 lks. wide, 2 ft. deep, drains WNW.
- 82.08 Intersect the Eighth Standard Parallel North.
Point for the closing cor. of secs. 3 and 4.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | |
|------|------|
| T41N | R40E |
| S 33 | |
| S 4 | S 3 |
| | CC |
| | T40N |
| | 1965 |
- raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
- from this corner
- The standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 41 N., R. 40 E., bears N. 89° 57' W., 16.74 chs. dist.
- The standard cor. of secs. 33 and 34, T. 41 N., R. 40 E., bears S. 89° 57' E., 23.36 chs. dist.