

## SUBDIVISION OF T. 40 N., R. 41 E.

## CHAINS

raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

from this corner

The standard sec. cor. of secs. 34 and 35, T. 41 N., R. 41 E., bears N. 89° 07' W., 12.42 chs. dist.

The standard  $\frac{1}{4}$  sec. cor. of sec. 35, T. 41 N., R. 41 E., bears S. 89° 07' E., 27.75 chs. dist.

From the cor. of secs. 27, 28, 33 and 34.

S. 0° 02' E., bet. secs. 33 and 34.

Over gently rolling land, sloping E., through medium undergrowth.

6.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 80° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R41E

$\frac{1}{4}$   
S 33 | S 34

1964

raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

43.20 Desert road, bears N. 15° E. and S. 15° W.

44.70 Wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.

58.30 Trail road, bears E. and W.

71.65 Fence, bears N. 89° 26' W. and S. 89° 26' E.

73.74 Intersect the N. bdy. of T. 39 N., R. 41 E.

Point for the closing cor. of secs. 33 and 34.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

CC

T40N R41E

S 33 | S 34

S 3

T39N

1964

raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

from this corner