

EIGHTH STANDARD PARALLEL NORTH, THROUGH R. 41 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T41N R41E
S 31 | S 32
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

Land, gently rolling to rolling.
Soil, sandy loam.
Undergrowth, sagebrush.

S. $89^{\circ} 37'$ W., along the S. bdy. of sec. 31.

Over rolling land, through medium undergrowth; asc. 120 ft. over an E. slope.

28.10 Trail road, bears NE. and SW.; asc. 100 ft. over an E. slope.

40.27 The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a stone, 10x6x4 ins., firmly set in a mound of stone and mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

SC
T41N R41E
 $\frac{1}{4}$ S 31
1964

bury the original cornerstone alongside the iron post.

S. $88^{\circ} 11'$ W., beginning new measurement.

Ascend 580 ft. over a SE. slope.

38.80 The standard cor. of T. 41 N., Rs. 40 and 41 E., monumented with a stone, 22x6x6 ins., firmly set in a mound of stone and plainly mkd. with 6 notches on the E., W. and N. faces.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.

SC
T41N
R40E R41E
S 36 | S 31
1964