

DEPENDENT RESURVEY, E. BDY., T. 41 N., R. 41 E.

CHAINS
40.27

The $\frac{1}{2}$ sec. cor. of secs. 7 and 12, monumented with a stone, 8x6x4 ins., firmly set in a mound of stone and mkd. $\frac{1}{2}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T41N
R41E R42E
 $\frac{1}{2}$
S 12 | S 7
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 33'$ W., beginning new measurement.

Ascend 100 ft. over a gently rolling S. slope.

40.30

The cor. of secs. 1, 6, 7 and 12, monumented with a stone, 20x8x4 ins., firmly set in a small mound of stone and mkd. with 1 notch on the N. face and 5 notches on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N
R41E R42E
S 1 | S 6
S 12 | S 7
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, gently rolling.
Soil, sandy loam and rocky.
Undergrowth, sagebrush.

N. $0^{\circ} 18'$ E., bet. secs. 1 and 6.

Over gently rolling land, through medium undergrowth.

11.80

Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.; asc. 70 ft. over gently rolling land.

40.68

The $\frac{1}{2}$ sec. cor. of secs. 1 and 6, monumented with a stone, 12x8x6 ins., firmly set in a mound of stone and mkd. $\frac{1}{2}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.