

## DEPENDENT RESURVEY, E. BDY., T. 42 N., R. 41 E.

CHAINS	
	Asc. 50 ft. over SE. slope.
41.40	Crest of flat-topped ridge, bears E. and W.; asc. 120 ft. over a gentle SE. slope.
79.05	Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.  <div style="text-align: center;">           T42N            R41E R42E            S 1   S 6            S 12   S 7            1964         </div>
	Land, rolling tableland. Soil, sandy loam, rocky. Undergrowth, sagebrush and shadscale.
	N. 0° 28' W., bet. secs. 1 and 6.  Over rolling tableland, through medium undergrowth.
3.40	Crest of flat-topped ridge, bears N. 80° E. and S. 80° W., desc. 470 ft. over a N. slope.
24.90	Wash, 20 lks. wide, 3 ft. deep, drains W.; asc. 290 ft. over a SW. slope.
26.80	Trail road, bears W. and N. 80° E.
38.60	Ledge, 15 ft. high, cont. over rolling ridge.
39.53	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.  <div style="text-align: center;">           T42N            R41E R42E            ¼            S 1   S 6            1964         </div>
65.00	Crest of ridge, bears N. 30° E. and SW.; desc. 300 ft. over a NW. slope.
79.05	Point for the cor. of Tps. 42 and 43 N., Rs. 41 and 42 E.; at proportionate distance; there is no remaining evidence of the original corner.