

DEPENDENT RESURVEY, W. BDY., T. 42 N., R. 41 E.

CHAINS		
	<p style="text-align: center;"> N1/16 S 7 1964 </p>	
	<p>Desc. 260 ft. over steep N. slope.</p>	
<p>30.80</p>	<p>Martin Creek, 50 lks. wide, 2 ft. deep, drains W.; asc. 160 ft. over broken SE. slope.</p>	
<p>38.96</p>	<p>The cor. of secs. 6 and 7, monumented with a stone, 18x12x6 ins., firmly set and dimly mkd. 1 notch on the N. face and 5 notches on the S. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <p style="text-align: center;"> T42N R40E R41E S 6 S 7 1964 </p> <p>bury the original cornerstone alongside the iron post.</p> <p>Land, S. ½, rolling tableland; N. ½, broken, low mountainous.</p> <p>Soil, sandy loam, rocky.</p> <p>Undergrowth, sagebrush and shadscale.</p>	
	<p>N. 0° 10' W., along the W. bdy. of sec. 6.</p>	
	<p>Over low mountainous land, through medium undergrowth; asc. 70 ft. over a SE. slope.</p>	
<p>5.30</p>	<p>Top of ascent on the E. slope of a rocky butte approximately 6.00 chs. from the top. Desc. 120 ft. over a NE. slope.</p>	
<p>19.48</p>	<p>Point for the S. 1/16 sec. cor. of sec. 6, at midpoint.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> S 1/16 S 6 1964 </p>	
	<p>raise a mound of stone, 3½ ft. base, 3 ft. high, E. of cor.</p>	
<p>19.70</p>	<p>Wash, 20 lks. wide, 2 ft. deep, drains E. 2.50 chs.; thence SE.; asc. 330 ft. over a SW. slope.</p>	