

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF  
T. 39 N., R. 42 E.

CHAINS	
40.60	Small wash, drains N. 60° W.
48.50	Small wash, drains N. 60° W.
79.06	<p>The cor. of secs. 3 and 4 on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy clay loam. Undergrowth, shadscale and budsage.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 38 N., R. 42 E., under Group No. 411.</p> <p>N. 3° 08' E., bet. secs. 32 and 33.</p> <p>Over mountainous land, through medium undergrowth; along an E. slope.</p>
2.80	Spur, slopes E.; continue along an E. slope.
21.00	Spur, projects N. 70° E.; desc. 110 ft. over a N. slope.
26.40	Wash, 10 lks. wide, 4 ft. deep, drains N. 70° E.
27.90	Trail road, bears N. 70° E. and S. 70° W.; asc. 210 ft. over a S. slope.
39.715	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T39N R42E           ½ S 32   S 33           1964</p>
40.60	Spur, slopes S. 60° E.; continue along an E. slope.
51.50	Begin descent over a N. slope; desc. 180 ft.
57.50	Wash, 50 lks. wide, 2 ft. deep, drains E.; asc. 70 ft. over a SE. slope.
66.30	Burma road, bears NE. and SW.; continue over rolling land.
75.54	<p>Point selected for the witness cor. of secs. 28, 29, 32 and 33, at a safe distance from the plans of expansion of the mining activity at the true corner point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>