

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 N., R. 43 E.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R43E S 3 S 2 1964</p> <p>raise a mound of broken concrete, 2 ft. base, 2 ft. high, W. of cor.</p>
71.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.
81.11	<p>The cor. of secs. 2 and 3 on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy loam. Undergrowth, sagebrush.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 38 N., R. 43 E., under Group No. 411.</p> <p>N. 0° 50' E., bet. secs. 33 and 34.</p> <p>Over gently rolling land, through medium undergrowth.</p>
39.69	<p>Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R43E S 33 S 34 1964</p> <p>raise a mound of broken concrete, 2 ft. base, 2 ft. high, W. of cor.</p>
48.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
62.60	Fence, bears S. 59° E. and N. 59° W.
64.30	Trail road, bears N. 25° E. and S. 25° W.
73.00	Enter bottom land, bears NE. and SW.
77.60	Kelly Creek, 20 lks. wide, 3 ft. deep, course S. 60° W.
79.38	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p>