

EIGHTH STANDARD PARALLEL NORTH, R. 43 E.

CHAINS

The standard SE. corner of T. 41 N., R. 43 E., monumented with an unmarked wooden post, 2x3x30 ins. long, with a steel fence post set alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T41N
R43E
<u>S 36</u>

1965

reset the original wooden post and steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2½ ft. high, NW. of cor.

N. 89° 09' W., along the S. bdy. of sec. 36.

Over rolling land, through medium undergrowth.

14.30 Layton Creek, 10 lks. wide, 4 ft. deep, course NW.

22.49 The closing cor. of T. 40 N., Rs. 43 and 44 E., hereinafter described.

32.00 Small wash, drains N.

39.31 The standard ¼ sec. cor. of sec. 36, monumented with a porphory stone, 24x10x6 ins., firmly set and plainly mkd. ¼ on the N. face, with steel fence post set alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T41N R43E
<u>¼ S 36</u>

1965

bury the original cornerstone alongside the iron post and reset the steel fence post N. of cor.

S. 89° 31' W., beginning new measurement.

Over gently rolling land.

39.93 Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T41N R43E
<u>S 35 S 36</u>

1965