

DEPENDENT RESURVEY OF THE W. BDY. OF T. 40 N., R. 44 E.

CHAINS		
5.28	The closing cor. of secs. 12 and 13, T. 40 N., R. 43 E., hereinafter described.	
	Desc. 170 ft.	
40.165	Point for the $\frac{1}{4}$ sec. cor. of sec. 7, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<div style="text-align: center;"> T40N R43E R44E $\frac{1}{4}$ S 7 1965 </div>	
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.	
	Desc. 50 ft. over a N. slope.	
45.24	The E. $\frac{1}{4}$ sec. cor. of sec. 12, T. 40 N., R. 43 E., hereinafter described.	
63.30	Wash, 10 lks. wide, 2 ft. deep, drains NW.	
72.20	Wash, 10 lks. wide, 4 ft. deep, drains W.; asc. 140 ft. over a SE. slope.	
80.33	The cor. of secs. 6 and 7, monumented with a stone, 10x5x5 ins., firmly set in a mound of stone and plainly mkd. with 5 notches on the S. face and 1 notch on the N. face.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<div style="text-align: center;"> T40N R43E R44E S 12 S 6 S 7 1965 </div>	
	bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.	
	Land, rolling. Soil, sandy clay and gravelly. Undergrowth, sagebrush and shadscale.	
	N. $14^{\circ} 43'$ E., along the W. bdy. of sec. 6.	
	Over rolling land, through medium undergrowth; asc. 10 ft.	
3.70	Ridge, bears E. and W.	