

## SUBDIVISION OF T. 40 N., R. 43 E.

## CHAINS

raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

Asc. 70 ft. over a NW. slope.

54.50 Spur, slopes SW.; desc. 70 ft. over a SE. slope.

60.30 Ravine, drains SW.; asc. 110 ft. over a SW. slope.

76.90 Intersect the W. bdy. of T. 40 N., R. 44 E.

Point for the closing cor. of secs. 25 and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

	T40N		
	R43E	R44E	
CC	S 25		S 30
	S 36		
	1965		

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
from this corner

The cor. of secs. 30 and 31, T. 40 N., R. 44 E., heretofore described, bears S.  $0^{\circ} 23'$  W., 7.39 chs. dist.

The  $\frac{1}{4}$  sec. cor. of sec. 30, T. 40 N., R. 44 E., heretofore described, bears N.  $0^{\circ} 23'$  E., 33.22 chs. dist.

Land, rolling.  
Soil, sandy clay and rocky.  
Undergrowth, sagebrush and shadscale.

The point for the E.  $\frac{1}{4}$  sec. cor. of sec. 36 is on the W. bdy. of T. 40 N., R. 44 E. and 40.00 chs. in latitude from the closing cor. of secs. 25 and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 5 ins. in the ground to bedrock and in a mound of stone to cap,  $3\frac{1}{2}$  ft. base, with brass cap mkd.

	T40N		
	R43E	R44E	
	$\frac{1}{4}$		
	S 36		
	1965		

from which

The  $\frac{1}{4}$  sec. cor. of sec. 31, T. 40 N., R. 44 E., heretofore described, bears S.  $0^{\circ} 30'$  W., 7.58 chs. dist.

The cor. of secs. 30 and 31, T. 40 N., R. 44 E., heretofore described, bears N.  $0^{\circ} 30'$  E., 32.61 chs. dist.